

Description

The PTX19 Industrial Rackmount Computer fits the standardized frame and enclosure for mounting multiple electronic modules.

Widely used for allowing denser hardware configuration without occupying excessive floorspace, requiring shelving, or industrial power, control and automation software.



Key Features

- Rugged modular steel bars are mounted directly to the rack
- Available with up to 7 Slots and 3 Drive Bays: Passive Backplane
- Low Power Industrial Rackmount with PICMG/PCISA board

Specifications

PTX19 INDUSTRIAL RACKMOUNT COMPUTER	
SPECS	PTX19
Expansion Slots	Up to 7 Slots
System	PICMG Core 2 Duo: 2x Ethernet 1.0Gb Ports, 2x USB 2.0, 2x RS232 Ports, 1x PS/2 PCISA Board: 2x Ethernet 1.0Gb, 3x USB 2.0, 2x RS232 Ports (RS422/485 Options), 1x PS/2
CPU	Core 2 Duo Mobil, Core Solo Mobile, Celeron Fanless
Operating System	Windows XP Pro, Windows XP Embedded, Windows 2000, Windows Vista, Windows 7, ROMDOS
Memory	1.0Gb to 2Gb DDR or DDR2
Storage Drives	2.5" SATA or PATA Hard Drives / 2.5" Solid State Drives / Industrial Compact Flash Cards
Media Drives	Slim DVD/DVD-RW/CD/CD-RW
Power Supply	110~240 VAC 250 Watt Power Supply, Approximately 75 Watts System Consumption
Temperature	0°~50°C (32°~122°F) Operating / -25°~60°C (-4°~140°F) Non-Operating
Relative Humidity	10% ~ 95% Non-Condensing
Shock	10G Operating / 15G Non-Operating
Vibration	1.0G from 57-2000 Hz Operating / 2.5G from 57-2000 Hz Non-Operating
Warranty	24 Month Limited Warranty. Extended Warranty Available, Contact Us For More Details

Dimensions

	PTX19
Height	6.9"
Width	17.3"
Depth	19.8"
Weight	23.1 lbs